

Technology that simply connects.

HAAS[®]
Nürnberg



Since over 70 years quality & innovation for the plumbing trade.

**SML
CONNECTIONS**



OHA-Combi-Claws

Item No.:	Size:	longitudinal force consistency:	Torque:	Pcs.
6400	DN 50	10 bar	18 - 20 Nm	10
6401	DN 70	10 bar	18 - 20 Nm	10
6402	DN 80	10 bar	20 - 23 Nm	10
6403	DN 100	10 bar	30 - 35 Nm	10
6404	DN 125	5 bar	30 - 35 Nm	10
6405	DN 150	5 bar	33 - 35 Nm	10
6406	DN 200	3 bar	40 - 50 Nm	2
6407	DN 250	1 bar	50 - 55 Nm	1
6409	DN 300	1 bar	50 - 55 Nm	1

Longitudinally locking and fire-proof locking point (galvanized steel) for SML cables and fittings. According to DIN EN 877 and 19522 for all OHA Rabbit, CV and CE connectors.

**STRONG
CONNECTION**

OHA-Rabbit-Connector

Item No.:	Size:	Torque:	Pcs.
6095	DN 50	6 Nm	45
6096	DN 70	6 Nm	50
6130	DN 75/80	6 Nm	50
6097	DN 100	6 Nm	45
6098	DN 125	6 Nm	20
6099	DN 150	6 Nm	20
6100	DN 200	6 Nm	20

Material Rubber: EPDM, resistant to aging and weathering according to DIN EN 681-1

Profile clamp made of stabilized chromium steel, with a screw for socket-free, cast-iron drainage pipes and fittings to DIN EN 877 and DIN 19522, axial force-locking up to 0.5 bar.



**Our assortment
you will find
in our catalog**



QUALITY PRODUCTS MADE BY HAAS - Innovative! **Permanently!** For sure!

Gießener Str. 5 • 90427 Nürnberg • Phone +49 911 9366-0 • www.haas.de • info@haas.de

All prices are net prices plus statutory VAT at the time of delivery! The general terms and conditions 01/2016 of Otto Haas KG apply, www.haas.de. Errors and changes reserved.